

LW 7605 COAXIAL

BASS:	1 x 6" bass (coaxial) speaker LW7605LF
TREBLE:	1 x 1" treble unit (coaxial) driver LW7603HF
HORN:	Directivity 90° x 90°
POWER:	200W AES/400W+50W Prg. Nominal impedance 8 ohm.
SENSITIVITY:	94dB/1W/1m free field SPL 117dB SPL 120dB with musical criteria
FREQUENCY RESPONSE:	(-10dB) 60 to 20.000 Hz.
SIZE:	20 x 20 x 20 cm
WEIGHT:	7,5 Kg.



This new unit will be introduced at Barcelona CineEurope 2015. It is a 6" coaxial driver two way full range cinema surround speaker, designed with installation easiness for the new multichannel 3D sound systems in mind. With its 90° x 90° directivity it can be installed at ceilings, as well as on usual on-wall applications.

This is a two way 225W unit, which includes an LW7711 U-bracket support that can be linked to our LW 7715 Top Support, and a Laser device to help adjusting the perfect aim of the system. As usual with all of the LW surround speakers, they can be painted in any RAL color needed by the customer.

The enclosure is mounted on a 60x60 cm. wisa birch plate, painted with poliurea, to swap with one of the tiles of the ceiling structure.

