

LW 8003-BI

Screen systems

| | |
|---------------------|---|
| BASS: | 2 x 15" bass unit LW8003LF |
| TREBLE: | 1 Line Array System with 4 x 6" + 4 x 1" drivers LW7501HF with passive filter inside |
| HORN: | 4 x Isophasic ABS horns, 120° x 8° each. With pan/tilt adjustment |
| POWER: | Bass system, 1400W AES/2800W Prg. 4 ohm. Medium/treble system 620W AES/1240W Prg. 4 ohm. |
| SENSITIVITY: | Complete assembly: SPL 132dB - SPL 133dB with musical criteria LF Unit: Sens. 101dB 1W/1m- Half space - SPL 132,5dB - SPL 135,5dB with musical criteria MHF unit: Sens. 98,7dB 1W/1m. Free field - SPL 126dB - SPL 129dB with musical criteria |
| FREQUENCY RESPONSE: | 28/22.000 Hz. For biamp cut off freq. please use our LW-8080 DSP Processor |
| SIZE: | 177,8 x 66 x 61,5 cm. |
| WEIGHT: | |



A screen system including LAT2014 (Line Array Technology), which combines professional compression drivers with true isophasic horns to achieve an extreme -3dB coverage throughout the whole audience area. 2 x 15" bass section plus a middle-treble section with Line Array Technology and 4 x 6" medium drivers plus 4 x 1" compression drivers + 4 x isophasic horns. For the biamp cut off frequency, please use our LW-8080 DSP Processor, which is delivered with all necessary presets, or a single crossover working at 150Hz.

